

SYSTEM AND METHOD FOR PROVIDING CUSTOMER SUPPORT

FIELD OF THE INVENTION

5 The present disclosure relates to a system and method for providing customer support. More particularly, the disclosure relates to a system and method for providing customer support to a peripheral device user at the peripheral device.

BACKGROUND OF THE INVENTION

10 When a user is having difficulty with an electrical device such as a peripheral device, the user can consult the vendor's user manual or, in business office contexts, consult a system administrator familiar with the device. In situations in which the user cannot resolve the problem with reference to the user manual or a system administrator, the user can call a customer support line, normally from a remotely
15 located telephone, which is maintained by the vendor to provide support from a customer support representative.

 Before such a call can be placed, the user must first locate the customer support telephone number, identify any authorization information that the customer support representative may require (*e.g.*, serial number, model number, *etc.*), call the
20 number, respond to all prompts put forth by an automated routing system, and wait in

a queue until an appropriate customer support representative becomes available. Once a representative is available, the user can communicate the problem to the representative, receive advice as to how to resolve the problem, and then apply the customer support representative's recommendations to the electrical device.

5 While this procedure can be effective, it can be frustrating for the user in situations in which the course of action recommended by the customer support representative does not resolve the problem. In such a case, the user normally must return to his or her telephone and place another call to the customer support line. Once this call is placed, the user must again go through all system prompts and wait in
10 the queue. In addition, once the user reaches the customer support representative, it often is a different representative from that to which the user had previously spoken. Therefore, the user must often re-describe the problem to the representative, as well as the failed attempt to resolve the problem. At this point, the user can receive further instructions as to how to fix the problem and again apply them to the malfunctioning
15 device. If this new course of action does not work, the user can again call the customer service line and repeat the process.

From the above, it can be appreciated that it would be desirable to have a system and method in which a device user can receive support from a customer support representative at the malfunctioning device such that the user can attempt to resolve the
20 problem while still maintaining communications with the representative in case the proposed solution does not work.

SUMMARY OF THE INVENTION

The present disclosure relates to a system and method for providing customer support to an electrical device user. The method comprises the steps of establishing a communications link between a customer support representative and the user with a customer support unit associated with the electrical device, and transmitting communications of the customer support representative to the user while the user is at the electrical device via the customer support unit.

The system comprises means for transmitting customer support representative communications across a network, and means for presenting the customer support representative communications to a user at the electrical device. In a preferred arrangement, the system comprises a customer support unit that is adapted to electrically connect to the electrical device, the customer support unit comprising a speaker and a display that are adapted to present audio and video data of a customer support representative to the user, and network interface devices that are adapted to transmit and receive communications across a network.

The features and advantages of the invention will become apparent upon reading the following specification, when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention can be better understood with reference to the following drawings. The components in the drawings are not necessarily to scale, emphasis instead being placed upon clearly illustrating the principles of the present invention.

5 FIG. 1 is a schematic view that illustrates a system for providing customer support.

 FIG. 2 is a schematic view that illustrates an example architecture of an electrical device shown in FIG. 1.

 FIG. 3 is a flow diagram that illustrates the operation of a web server module
10 shown in FIG. 2.

 FIG. 4 is a schematic view that illustrates an example architecture of a computing device shown in FIG. 1.

 FIG. 5 is a flow diagram that illustrates the operation of a control module shown in FIG. 4.

15 FIGS. 6A-6C provide views of a flow diagram that illustrates a method for receiving customer support with the system shown in FIG. 1.

 FIG. 7 is a perspective view of an electrical device that can be used in the system shown in FIG. 1.

DETAILED DESCRIPTION

20 Referring now in more detail to the drawings, in which like numerals indicate corresponding parts throughout the several views, FIG. 1 illustrates a system 100 for providing customer support. The system 100 can comprise an electrical device 102 that,

by way of example, comprises a peripheral device. When the electrical device 102 is a peripheral device, it can be substantially any peripheral device with which a user may require support. For example, the peripheral device can comprise a printer, photocopier, facsimile machine, scanner, digital sender, multi-function peripheral, *etc.* As indicated in FIG. 1, the electrical device 102 can include a customer support unit 104, the purpose for which is described below.

The electrical device 102 is connected to a network 106 that, by way of example, comprises the Internet. Through such a connection, the electrical device 102 can post data to the Internet and receive data (as well as commands) from a remote computing device 108 of a customer support representative. By way of example, the computing device 108 can comprise a desktop computer that includes a web camera 110. Although shown and described as comprising a desktop computer, it will be understood from the present disclosure that the computing device can comprise a dedicated customer support device specifically adapted to provide customer support to device users.

FIG. 2 is a schematic view illustrating an example architecture for the electrical device 102 shown in FIG. 1. As indicated in FIG. 2, the electrical device 102 comprises a processing device 200, user interface devices 202, device operation hardware 204, memory 206, a customer support display 208, a video camera 210, a microphone 212, a speaker 214, network interface devices 216, and a local interface 218 to which each of the other components electrically connects. The processing device 200 is adapted to execute commands stored in memory 206. The processing device 206 can comprise a general-purpose processor, a microprocessor, one or more application-specific integrated circuits (ASICs), a plurality of suitably configured digital logic gates, and

other well known electrical configurations comprised of discrete elements both individually and in various combinations to coordinate the overall operation of the peripheral device 102. The user interface devices 202 typically comprise interface tools with which the user, *i.e.*, customer, can communicate commands to the electrical device

5 102. By way of example, the devices 202 can comprise various function keys with which the settings of the device 102 can be changed, and a display screen with which information (*e.g.*, device status and settings) can be communicated to the customer. The device operation hardware 404 comprises the various mechanisms that are used to perform the various functionalities of the electrical device 102. For instance, where the

10 device 102 is a photocopier, this hardware can include a document feeder, scanner, *etc.* used by the device to produce photocopies of an original document.

The customer support display 208 normally comprises a display screen with which the customer can view video of a customer support representative. By way of example, this display 208 can comprise a touch-sensitive display with which commands

15 can be entered by the customer. The video camera 210 normally comprises a digital camera (such as web camera) that is adapted to capture video images of the customer that can be transmitted to the customer support representative. The network interface devices 216 are adapted to facilitate communications across the network 106 (*e.g.*, Internet) and therefore can comprise a modem or other data transmitting/receiving

20 device. In particular, the network interface devices 216 are adapted to transmit audio and video of the customer collected via the microphone 212 and video camera 210 to the customer support representative, and to receive audio and video from a customer support representative for presentation to the user.

The memory 206 includes an operating system 220, a communications module 222, and a web server module 224. The operating system 220 contains the various commands used to control the general operation of the electrical device 102. The communications module 222 comprises software and/or firmware that is adapted to, in conjunction with the network interface devices 216, facilitate communications over the network 106 (*e.g.*, Internet) and, more particularly, to transmit and receive audio and video data. The web server module 224 comprises software and/or firmware that is adapted to collect and format information about the status and settings of the electrical device 102, such that this information, with the customer's permission, can be presented to the customer support representative.

FIG. 3 is a flow diagram that illustrates the operation of the web server module 224. With reference to block 300, the web server module 224 collects information as to the status and settings of the electrical device 102. For instance, the module 224 can collect information as to the configuration of the electrical device 102, all device settings that have been selected, and any error messages (*e.g.*, from an error log maintained by the device 102) that reflect any malfunctions the device has experienced. Once this information is collected, it is stored by the module 224, as indicated in block 302. The stored information can be formatted, as indicated in block 304, for insertion into one or more web pages generated by the web server module 224. By way of example, the web pages can comprise standardized web page templates that include data fields that the web server module 224 populates with the collected device information. After the information is formatted, the web server module 224 generates the one or more web pages that identify the current status and settings of the electrical device 102, as

indicated in block 306. In that the status and settings of the device 102 can change, flow returns to block 300 from block 306 such that the web pages are continually updated by the web server module 224. This updating can occur upon detection of changes to the status or settings of the device 102 and/or according to a predetermined time schedule.

- 5 As is discussed below, the web pages can be made available to a customer support representative so as to share information as to the status and settings of the electrical device 102 with the representative. In addition, the web pages can, optionally, be displayed to the customer with the customer service display 208.

10 It is to be noted that although the electrical device 102 has been described and shown as integrating the customer support hardware, software, and/or firmware described above, it will be appreciated that this hardware, software, and/or firmware can be embodied within a device (*e.g.*, customer support unit 104) that is separate and independent from, but applied to, the electrical device. In such a case, however, the electrical connections indicated in FIG. 2 are still applicable and the functionality

15 described herein is the same.

FIG. 4 is a schematic view illustrating an example architecture for the computing device 108 shown in FIG. 1. As indicated in FIG. 4, the computing device 108 comprises a processing device 400, user interface devices 402, memory 404, a display device 406, a video camera 408, a microphone 410, a speaker 412, network interface devices 414, and a local interface 416 to which each of the other components electrically

20 connects. The processing device 400 is adapted to execute commands stored in memory 404 and typically comprises one or more central processing units (CPUs). The user interface devices 402 typically comprise interface tools with which the user, in this case

a customer support representative, can communicate commands to the computing device 108. By way of example, the interface devices 402 can comprise a keyboard and mouse.

The display device 406 normally comprises a monitor with which the customer support representative can visually interface with the computing device 108. As is described below, this display device 406 can be used to present to the representative video images of a customer that is having a problem with an electrical device 102. The video camera 408 normally comprises a digital camera (such as web camera 110 shown in FIG. 1) that is adapted to capture video images of the customer support representative so that these images can be transmitted to the customer. Typically, the microphone 410 and speaker 412 form part of a headset the customer service provider wears, although it is to be understood that these components could be separate from such a headset and furthermore, separate from each other. The network interface devices 414 are adapted to facilitate communications across the network 106 (e.g., Internet) and therefore can comprise a modem or other data transmitting/receiving device.

As identified in FIG. 4, memory 404 comprises an operating system 418, a communications module 420, and a control module 416. The operating system 418 contains the various commands used to control the general operation of the computing device 108. The communications module 420 comprises software and/or firmware that is adapted to facilitate communications over the network 106 (e.g., Internet) and, more particularly, to transmit and receive video and audio across the network such that audio and video can be exchanged between the customer support representative and the customer. As is described in greater detail below, the control module 422 comprises software and/or firmware that is adapted to permit the customer support representative

to determine the settings and status of the electrical device 102. In addition, the control module 422 permits the customer support representative to, when authorized, exercise control over the electrical device 102 such that the representative can change settings of the electrical device in an effort to correct a problem the customer is experiencing.

5 FIG. 5 is a flow diagram that illustrates the operation of the control module 422. With reference to block 500, the control module 422 transmits a request to access the web pages generated by the web server module 224 of the electrical device 102. As described above, this transmission is achieved through cooperation between the communications module 420 and network interface devices 414. Assuming the
10 customer support representative has authorization to access the web pages, the web pages can be accessed by the control module 422, as indicated in block 502. Once accessed, the web pages can be displayed to the customer support representative, e.g., with display device 406 as indicated in block 504. The customer support representative can then review this information to gain insight as to the problem the customer is
15 experiencing. If the customer support representative determines one or more sources of the problem, the representative can, with the customer's permission, make adjustments to the electrical device's settings via the control module 222, for instance by manipulation of a virtual control panel. In such a situation, the control module 422 receives commands of the customer support representative, as indicated in block 506, to
20 change the settings of the electrical device 102. These commands are then transmitted to the electrical device 102, as indicated in block 508. As is described below, these commands are received by the electrical device 102 and the settings of the device changed as if they were directly input by the customer.

Various software and/or firmware modules have been described herein. It is to be understood that these modules can be stored and transported on any computer-readable medium for use by or in connection with an instruction execution system, apparatus, or device, such as a computer-based system, processor-containing system, or other system that can fetch the instructions from the instruction execution system, apparatus, or device and execute the instructions. In the context of this document, a “computer-readable medium” can be any means that can contain, store, communicate, propagate, or transport the program for use by or in connection with the instruction execution system, apparatus, or device.

The computer readable medium can be, for example but not limited to, an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, apparatus, device, or propagation medium. More specific examples (a nonexhaustive list) of the computer-readable medium would include the following: an electrical connection having one or more wires, a portable computer diskette, a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM or Flash memory), an optical fiber, and a portable compact disc read-only memory (CDROM). Note that the computer-readable medium could even be paper or another suitable medium upon which the program is printed, as the program can be electronically captured, via for instance optical scanning of the paper or other medium, then compiled, interpreted or otherwise processed in a suitable manner if necessary, and then stored in a computer memory.

Operation of the system 100 will be discussed with reference to FIGS. 6A-6C and 7. More particularly, the following discussion describes a method for providing

customer support to a customer with the system 100 shown in FIG. 1. With reference to block 600 of FIG. 6A, a customer can experience a problem with an electrical device 102 that he or she cannot resolve. The customer can then initiate contact with a customer support representative (CSR), as indicated in block 602. This normally entails
5 the customer selecting a call button of the user interface devices 202. By way of example, such a call button can comprise a "soft" key presented to the user via the customer support display 208. With reference to FIG. 7, this display 208 can be integrated into the customer support unit 104. By selecting such a button or key, a service request is transmitted across the network 106 with the network interface devices
10 216 and routed to a customer support representative. A communication link is then established between the representative and the customer, as indicated in block 604.

At this point, audio and video data of the customer support representative are provided to the customer and vice versa, as indicated in block 606, as in a common video conferencing context. In particular, with reference to FIG. 7, video of the
15 customer support representative can be provided in the customer support display 208 and audio of the representative can be provided with the speaker 214. As mentioned above, this audio and video data can be collected by the representative's computing device 108 with the microphone 410 and video camera 408, respectively. In similar manner, audio and video of the user can be collected by the microphone 212 and video
20 camera 210 both of which, for example, being integrated into the customer support unit 104. Through this exchange of audio and video, the customer support representative and user can communicate with each other, as indicated in block 608. More specifically, the representative and the user can communicate with each other while the user is still

positioned at the electrical device 102. Accordingly, the user can directly apply the recommendations of the representative without terminating communications with the representative. In addition, through the provision of video, the customer support representative and user can communicate with each other visually such that information
5 can be conveyed between them more effectively than with audio alone.

As identified above, the system 100 is configured such that the customer support representative can view the status and settings of the electrical device 102 to diagnose and potentially correct the problem being experienced. Normally, as a security precaution, the customer support representative first needs authorization from the
10 customer to obtain this access. Accordingly, the customer support representative can first request permission from the customer to access the status and settings information, as indicated in block 610. The customer can then determine whether he or she would like to provide this authorization, as indicated in decision element 612. By way of example, the user can authorize the representative to obtain this access by selecting an
15 authorization grant button (not shown) that is presented as a soft key to the customer via the customer support display 208.

If the user either chooses not to extend this access, or where the electrical device 102 is configured such that this access cannot be extended (*e.g.*, as a security precaution), flow continues to block 614 of FIG. 6B at which the customer support
20 representative consults the customer as to how to overcome the problem being experienced. Such consultation normally comprises oral instructions given to the user as in the typical customer support call setting. In addition, however, the representative can further show the customer how to fix the device 102 in applicable situations due to the

transmission of video data. Once having received the instructions, the customer can attempt to resolve the problem, as indicated in block 616. The customer can then attempt to fix the device 102 without terminating communications with the representative. Accordingly, the customer need not travel back and forth between a
5 telephone and the electrical device 102 to apply the representative's recommendations.

As indicated in decision element 618, if the customer's actions resolve the problem, flow continues to block 622 at which the communication link with the customer support representative is broken and flow is terminated. If, on the other hand, the problem is not resolved, flow continues to decision element 620 where, based upon
10 the representative's advice, the customer can determine whether to continue to receive instructions from the representative and try other courses of action. If so, flow returns to block 614. If not, for instance in a situation where the problem requires a visit from a technician, flow continues to block 622 where the communication link is broken and flow is terminated.

15 With reference back to decision element 612 in FIG. 6A, if the customer support representative is given the authorization to view the device status and settings, flow continues to block 624 in FIG. 6C at in which the representative views the status and settings. As described above, this information can be presented to the representative with one or more web pages generated and posted by the web server module 224 of the
20 electrical device 102. By reviewing these pages, the customer support representative can determine the configuration of the device 102, receive diagnostic information about the device, as well as view the settings selected by the user for the device.

As indicated in decision element 626, if a mere configuration and/or settings

change is needed, flow continues to decision element 628 where the customer can determine whether to give the representative authorization to change the settings. If the customer decides not to (or cannot) provide this authorization, the flow continues to block 638 and the customer support representative consults the customer as to how to overcome the problem in similar manner to that described above. Once having received the instructions, the customer can attempt to resolve the problem as indicated in block 640, and if the customer's actions resolve the problem (element 642), flow continues to block 646 at which the communication link is broken and flow terminated. If, on the other hand the problem is not resolved, flow continues to decision element 644 where the customer can determine to receive more consultation with flow returning to block 638, or to try another solution (*e.g.*, technician visit) with flow continuing to block 646.

With reference back to decision element 628, if the problem is one in which configurations and/or a settings change would resolve the problem, and the customer support representative is provided with authorization to change the setting, the representative can then change the settings, as indicated in block 630. As noted above, this change can be made by the representative by manipulating a virtual control panel or otherwise changing the information contained in the generated web pages. If the problem is resolved, as indicated in block 632, the communication link can be broken, as indicated in block 634, and flow is terminated.

Returning to decision element 626, if the customer support representative determines that a mere configuration and/or settings change will not resolve the problem, the representative, with the customer's assistance, can determine whether a technician visit is needed, as indicated in decision element 636. If so, flow continues to

block 646 at which the communications link is terminated, and the customer support representative or customer can make arrangements for a service call in which a technician will visit the user's premises and resolve the problem.

While particular embodiments of the invention have been disclosed in detail in
5 the foregoing description and drawings for purposes of example, it will be understood by those skilled in the art that variations and modifications thereof can be made without departing from the scope of the invention as set forth in the following claims.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213